



[www.FGWilson.com](http://www.FGWilson.com)

# P1350P1/P1500E1

## Output Ratings

Voltage, Frequency	Prime	Standby
400V, 50 Hz	1350.0 kVA / 1080.0 kW	1500.0 kVA / 1200.0 kW
	- / -	- / -

Ratings at 0.8 power factor.

Please refer to the output ratings technical data section for specific generator set outputs per voltage.

## Prime Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

## Standby Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

## Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) Air Inlet Temp, 100m (328 ft) A.S.L. 30% relative humidity.

Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.





Image for illustration purposes only.

## Ratings and Performance Data

**Engine Make & Model:** Perkins® 4012-46TWG3A

**Alternator manufactured for FG Wilson by:** Leroy Somer

**Alternator Model:** LL8224L

**Control Panel:** PowerWizard 1.1+

**Base Frame:** Heavy Duty Fabricated Steel

**Circuit Breaker Type:** 3 Pole ACB - Option

**Frequency:** 50 Hz 60 Hz

**Engine Speed: RPM** 1500 -

**Fuel Tank Capacity:** litres (US gal) -

**Fuel Consumption:** l/hr (US gal/hr)

(100% Load)

- Prime	279.2 (73.8)	-
- Standby	313.4 (82.8)	-

## Available Options

FG Wilson offer a range of optional features to tailor our generating sets to meet your power needs. Options include:

- Upgrade to CE Certification
- A wide range of Sound Attenuated Enclosures
- A variety of generating set control and synchronising panels
- Additional alarms and shutdowns
- A selection of exhaust silencer noise levels

For further information on all of the standard and optional features accompanying this product please contact your local Dealer or visit: [www.FGWilson.com](http://www.FGWilson.com)

## Dimensions and Weights

Length (L) mm (in)	Width (W) mm (in)	Height (H) mm (in)	Dry kg (lb)	Wet kg (lb)
4888 (192.4)	1895 (74.6)	2450 (96.5)	9246 (20384)	9447 (20827)

Dry = With Lube Oil

Wet = With Lube Oil and Coolant

Ratings in accordance with ISO 8528, ISO 3046, IEC 60034, BS5000 and NEMA MG-1.22. Generating set pictured may include optional accessories.

Engine Technical Data		
No. of Cylinders / Alignment:		12 / Vee
Cycle:		4 Stroke
Bore / Stroke: mm (in)		160.0 (6.3)/190.0 (7.5)
Induction:		Turbocharged
Cooling Method:		Water
Governing Type:		Electronic
Governing Class:		ISO 8528
Compression Ratio:		13.0:1
Displacement: l (cu. in)		45.8 (2797.5)
Moment of Inertia: kg m <sup>2</sup> (lb/in <sup>2</sup> )		19.30 (65951)
Engine Electrical System:		
- Voltage / Ground		24/Negative
- Battery Charger Amps		40
Weight: kg (lb)	- Dry	4440 (9788)
	- Wet	4604 (10150)

Performance	50 Hz	60 Hz
Engine Speed: rpm	1500	-
Gross Engine Power: kW (hp)		
- Prime	1200.0 (1609.0)	-
- Standby	1314.0 (1762.0)	-
BMEP: kPa (psi)		
- Prime	2094.0 (303.7)	-
- Standby	2293.0 (332.6)	-

Fuel System				
Fuel Filter Type:		Replaceable Element		
Recommended Fuel:		Class A2 Diesel or BSEN590		
Fuel Consumption: l/hr (US gal/hr)				
	110%	100%	75%	50%
Prime	Load	Load	Load	Load
50 Hz	313.4 (82.8)	279.2 (73.8)	210.2 (55.5)	152.3 (40.2)
60 Hz	-	-	-	-
	100%	75%	50%	
Standby	Load	Load	Load	
50 Hz	313.4 (82.8)	232.0 (61.3)	164.2 (43.4)	
60 Hz	-	-	-	

(Based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)

Air Systems	50 Hz	60 Hz
Air Filter Type: Replaceable Element		
Combustion Air Flow: m <sup>3</sup> /min (cfm)		
- Prime	108.0 (3814)	-
- Standby	114.0 (4026)	-
Max. Combustion Air Intake Restriction: kPa (in H <sub>2</sub> O)		
	4.0 (16.1)	-

Cooling System	50 Hz	60 Hz
Cooling System Capacity: l (US gal)		
	196.0 (51.8)	-
Water Pump Type: Centrifugal		
Heat Rejected to Water & Lube Oil:		
kW (Btu/min)		
- Prime	395.0 (22463)	-
- Standby	441.0 (25079)	-
Heat Radiation to Room: Heat radiated from engine and alternator		
kW (Btu/min)		
- Prime	140.7 (8001)	
- Standby	158.8 (9031)	

Radiator Fan Load: kW (hp)	51.0 (68.4)	-
Radiator Cooling Airflow: m <sup>3</sup> /min (cfm)	1620.0 (57210)	-
External Restriction to Cooling Airflow: Pa (in H <sub>2</sub> O)	250 (1.0)	-

Designed to operate in ambient conditions up to 50°C (122°F).  
Contact your local FG Wilson Dealer for power ratings at specific site conditions.

Lubrication System		
Oil Filter Type:		Spin-On, Full Flow
Total Oil Capacity: l (US gal)		177.0 (46.8)
Oil Pan: l (US gal)		157.5 (41.6)
Oil Type:		API CH4 15W-40
Oil Cooling Method:		Water

Exhaust System	50 Hz	60 Hz
Maximum Allowable Back Pressure: kPa (in Hg)		
	5.0 (1.5)	-
Exhaust Gas Flow: m <sup>3</sup> /min (cfm)		
- Prime	240.0 (8476)	-
- Standby	240.0 (8476)	-
Exhaust Gas Temperature: °C (°F)		
- Prime	474 (885)	-
- Standby	474 (885)	-



## General Information

### Documentation

A full set of operation and maintenance manuals and circuit wiring diagrams.

### Generating Set Standards

The equipment meets the following standards: BS5000, ISO 8528, ISO 3046, IEC 60034, NEMA MG-1.22.

FG Wilson is a fully accredited ISO 9001 company.

### Warranty

All prime equipment carries a one year manufacturer's warranty with unlimited hours or two year manufacturer's warranty limited to 6,000 running hours. Standby equipment, limited to 500 running hours per year, has a three year manufacturer's warranty.

### Dealer contact details:

### FG Wilson manufactures product in the following locations:

Northern Ireland • Brazil • China • India • USA

With headquarters in Northern Ireland, FG Wilson operates through a Global Dealer Network.

To contact your local Sales Office please visit the FG Wilson website at [www.FGWilson.com](http://www.FGWilson.com).

FG Wilson is a trading name of Caterpillar (NI) Limited.

In line with our policy of continuous product development, we reserve the right to change specification without notice.

P1350P1 / P1500E1/4PP/0514/GB