

let's talk!

Inverter INVW400

- case for wall mounting
- small and strong
- without 50 Hz transformer
- potential free
- sinewave
- short-circuit protected
- overload protected

Picture may differ from actual device



Specifications

General

Electrical safety	EN 60950, VDE 0805 overload and short-circuit protected
Efficiency	about 85%, nominal load
Galvanic isolation	3.75 kV _{DC}
EMC (emission)	EN 50081-1 Curve EN 55022B
EMC (immunity)	EN 50082-2

Operating temperature -25 to +45 °C non condensing

Input

INVW400-24 24 (19 - 31) V_{DC}

Output

Voltage	230V _{AC} (115V _{AC} upon request)
Frequency	50 Hz, sinewave processor controlled (60Hz upon request)
Power	400 VA, 320W
Power factor	0.8
Load range	0 - 100%
Crestfactor	>2.5
Harmonic distortion	<3%

Signals/Operation

Optical signals	Power/PG, Overload/OVL
Signal output	voltage free alarm contact
Operation	switch

Optional:

Control input	optocoupler input for remote operation
---------------	---

Warranty 24 months

Housing

Size	wall mounting case
(W x D x H)	270 x 115 x 255 (mm)
Weight	app. 5kg
Classification	IP 54
Ventilation	convection via heatsink on wall side

Electrical connections

Connectors	bottom connectors
DC-Input	Harting connector HAN Q5, 3-pole
AC-Output	Harting connector HAN Q5, 3-pole
Signals	Binder round connector DIN 45322 (Harting HAN 80 5-pole opt.)
Earthing	via Harting HAN Q5 (DC-IN), earthing screw on the case

Order Code

e.g. INVW400-24 – 230 - 1

Type	P / VA	U _{in} / VDC	U _{out} / VAC	Options
INV	W	400	24	
			230	1, 5
			115	

Separate values by hyphen (-), append options where applicable

Options:

 1: 60Hz f_{OUT}

5: HAN 80 input for remote operation